

What does autooff mean in an optical power meter



Overview

If the icon "AUTOOFF" appears in the screen, the device will automatically turn off if there are no operations within 10 minutes. This is useful, if only a single sweep is performed. The DUT does not heat up unnecessarily. When performing a continuous measurement, it is considered to deactivate the automatic output power off. While in power-on state, short press it (for less than 3 seconds) to enable or disable AUTOOFF function. If the icon "AUTOOFF" doesn't appear in the screen, it indicates. The PM-4212 is four channel optical power meter, designed for continuous measurement of optical lines or for fiber optics work station for measurement optical power of various devices. PM-4212 is assembled with USB port and Ethernet port for communication with control application. According to an order scales can be calibrated. AutoOff is disabled by default.

Article Content

\$CheckUnits ON/OFF and AutoOn/AutoOff

\$CHECKUNITS AutoOn/AutoOff overrides the setting in the Preferences dialog. To ensure that automatic unit checking is on, place the following directive at the top of the EES file.

TnneLab ST AutoPowerOff (ToneLab ST_APO_C1)

If there is a signal at the INPUT jack or if the ToneLab ST is connected to a computer with a USB cable, the auto power-of function will not be activated, even if no operation is performed.

USER MANUAL

Taring does not extend measuring range, but only subtracts tare value from mass value of a sample placed on the pan. To make the control of a load on the pan easier and to avoid exceeding ...

Leica Geosystems SNLL121 : Owner manual

Functions ON/OFF Function AutoOff The laser plummet is switched off automatically after four minutes. Lalot05 This function is always active. Press briefly for switching on the laser plummet. 6 SNLL121 ...

Circuit/Software that allow Attiny 85 or other Arduino to power off itself

Circuit/Software that allow Attiny 85 to be powered on with a button and later power off itself. With this circuit your microcontroller consume no power until a button is pressed.

Honeywell Thor VM1 AutoOff, Auto-off, AutoOff Timeout

- If the shutdown when truck power lost option is selected, the timeout period begins when the UPS battery indicates it is no longer receiving external power. The timeout period is reset if vehicle power ...

RY3200 Optical Power Meter

If the icon "AUTOOFF" appears in the screen, the device will automatically turn off if there are no operations within 10 minutes. If the icon "AUTOOFF" doesn't appear in the screen, it indicates that ...

M6CF SPL Meter Noise Meter with Backlit Data Hold AutoOff Function

Product Summary: M6CF SPL Meter Noise Meter with Backlit Data Hold AutoOff Function From HIEUOCGR

Power Output Auto Off

When performing a continuous measurement, it is considered to deactivate the automatic output power off feature, because otherwise the source is powered down between each sweep run.

PM-4212 series Pocket Optical Power Meter

Do not disconnect the master patch cords from the light source and the power meter. If it happens, the measurement is lost, and you have to start again from beginning.

Annoying SnapOn Multimeter AutoOff

To disable autopower off hold down the FUNCTION button while turning the instrument on. Continue to hold the button down until the power icon turns off on the LCD (approximately 2 seconds)

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://automationauthoritiesolar.co.za>

Email: info@automationauthoritiesolar.co.za

Phone: +27 82 547 3961

Address: 15 Quantum Street, Technopark, Centurion, 0157, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

