

What mode does the MM850 optical module have



Overview

The eSFP-GE-SX-MM850 optical module is a Huawei Gigabit multimode optical module with DOM/DDM support, which is packaged in an SFP package with a center wavelength of 850 nm. When used with multimode optical fiber (LC/PC-LC/PC OM2), the transmission distance can reach up to 550 m, the transmission. Want to learn more?

Looking for something else?

This H3C® SFP-GE-SX-MM850-A compatible SFP transceiver provides 1000Base-SX throughput up to 550m over multi-mode fiber (MMF) using a wavelength of 850nm via an LC connector. It is guaranteed to be 100% compatible with the equivalent H3C® transceiver. Designed for extended temperatures (-40°C to 85°C), it includes Digital Optical Monitoring (DOM) and. This H3C SFP-GE-SX-MM850-A optics is a high performance and cost-effective small form factor pluggable transceiver. No power injector is provided with the AP. See "Connecting the AP to the power source" for the.

Article Content

H3C SFP-GE-SX-MM850-A MANUAL Pdf Download | ManualsLib

Installing the AP IMPORTANT: To ensure radio coverage, have the AP installed by technical personnel as a best practice. When you install the AP, follow these restrictions and guidelines: • The AP is large ...

H3C SFP-GE-SX-MM850-A Datasheet

This H3C SFP-GE-SX-MM850-A optics is a high performance and cost-effective small form factor pluggable transceiver. It is suitable for 1000BASE-SX Gigabit Ethernet and 1G Fibre Channel ...

XG-SFP-SR-MM850 10GBASE-SR SFP+ 850-nm 300-m DOM Duplex LC MMF Optical ...

The XG-SFP-SR-MM850 is aligned to IEEE 10GBASE-SR optical specifications and supports a link length of up to 300 m (984.25 ft., with OM3 optical cables) or 400 m (1312.34 ft., with OM4 optical ...

SFP-GE-SX-MM850-IN

Home Products Transmission Switches Optical Modules SFP-GE-SX-MM850-IN Gigabit Multi-Mode 500m Optical Module Specification

H3C SFP-XG-SX-MM850-E 10GBASE-SR SFP+ Module, Multi-Mode ...

It supports multi-mode fiber with a reach of 300m via a duplex LC connector. Designed for extended temperatures (-40°C to 85°C), it includes Digital Optical Monitoring (DOM) and guarantees full ...

H3C SFP-XG-SX-MM850-E 10GBASE-SR SFP

It supports multi-mode fiber with a reach of 300m via a duplex LC connector. Designed for extended temperatures (-40°C to 85°C), it includes Digital Optical ...

SFP-GE-SX-MM850-IN 1.25G Multi-Mode 550m SFP Optical ...

025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved. *Product specifications and availability are subject to change without notice. *Despite our best efforts, technical or typographical errors may ...

SFP-GE-SX-MM850

Overview 1. Gigabit Ethernet 2. Fiber Channel 3. Switch to Switch interface 4. Switched backplane applications 5. Router/Server interface 6. Other optical transmission systems

Huawei eSFP-GE-SX-MM850 Gigabit Optical Module Overview

The eSFP-GE-SX-MM850 optical module is a Huawei Gigabit multimode optical module with DOM/DDM support, which is packaged in an SFP package with a center wavelength of 850 nm. ...

Sfp-ge-sx-mm850-a-c Datasheet

This H3C® SFP-GE-SX-MM850-A compatible SFP transceiver provides 1000Base-SX throughput up to 550m over multi-mode fiber (MMF) using a wavelength of 850nm via an LC connector.

Support

You can choose optical modules as needed for data transmission over optical fibers. The optical modules include optical transmitters, optical receivers, transceivers, and transponders.

XG-SFP-SR-MM850 10GBASE-SR SFP+ 850-nm 300-m DOM ...

The XG-SFP-SR-MM850 is aligned to IEEE 10GBASE-SR optical specifications and supports a link length of up to 300 m (984.25 ft., with OM3 optical cables) or 400 m (1312.34 ft., with OM4 optical ...

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://automationauthoritysolar.co.za>

Email: info@automationauthoritysolar.co.za

Phone: +27 82 547 3961

Address: 15 Quantum Street, Technopark, Centurion, 0157, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

